

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

Plasticast PT investment

Revision Revision date 2016-07-05

SECTION 1: Idea	ntification of the subst	ance/mixture and of tl	he company/undertaking

1.1. Product identifier

Product name Plasticast PT investment

Plasticast PT investment 070516 C506 Product code

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph

Address 3535 Briarfield Boulevard.

Maumee, OH 43537 USA

Web www.ransom-randolph.com

Telephone +1 (419) 865-9497 Fax +1 (419) 865-9997 **Email** RR.SDS@dentsply.com

Email address of the competent person

RR.SDS@dentsply.com

USA +1 419 865 9497

1.4. Emergency telephone number

Emergency telephone number

Company Ransom & Randolph Co.

07:30 to 16:30 (Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification -

Xn: R48/20

1999/45/EC

Symbols: Xn: Harmful.

Main hazards

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

2.1.2. Classification - EC

1272/2008

STOT RE 1: H372;

2.2. Label elements

Hazard pictograms



Signal Word

Hazard Statement

STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.

Precautionary Statement:

Prevention

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash (hands) thoroughly after handling.

P270 - Do no eat, drink or smoke when using this product.

Revision 1
Revision date 2016-07-05

2.2. Label elements

Precautionary Statement: Response	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement:	P501 - Dispose of contents/container to local and national regulations
Disposal	
0.0.0455	

2.3. Other hazards

Other hazards	Product contains respirable crystalline silica (RCS).
	Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No. CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
silica (cristobalite) more than 10 %	14464-4	6-1 238-455-4		40 - 70%	Xn; R48/20	
Quartz	14808-6	0-7 238-878-4		20 - 40%	Xn; R48/20	
Magnesium Oxide	01309-4	3-4 215-171-9		5 - 10%	Xn; R20 Xi; R37/38	

EC 1272/2008

		REACH Registration Number	Conc.	Classification	M-factor.
14464-46-1	238-455-4	Number		STOT RE 1: H372;	
14808-60-7	238-878-4		20 - 40%	STOT RE 1: H372;	
			14464-46-1 238-455-4	14464-46-1 238-455-4 40 - 70%	14464-46-1 238-455-4 40 - 70% STOT RE 1: H372;

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

Quartz "fine fraction" >= 10 % w/w / CAS 14808-60-7, EC No 238-878-4 / STOT RE1: H372.

Silica (Cristobalite) "fine fraction" >= 10 % w/w / CAS 14464-46-1, EC No 238-455-4 / STOT RE1: H372.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash with soap and water.	
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	lay cause irritation to respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin.	
Ingestion	May cause irritation to mucous membranes.	

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.	
Eye contact	Seek medical attention if irritation or symptoms persist.	
Skin contact	Seek medical attention if irritation or symptoms persist.	
Ingestion	Seek medical attention if irritation or symptoms persist.	



Revision

Revision date 2016-07-05

		sion date 2016-07-05
SECTION 5: Firefighting me	easures	
5.1. Extinguishing media		
	Use extinguishing media appropriate to the surrounding fire conditions.	
5.2. Special hazards arising from	m the substance or mixture	
	Burning produces irritating, toxic and obnoxious fumes.	
5.3. Advice for firefighters		
	Self-contained breathing apparatus. Wear suitable protective clothing.	
SECTION 6: Accidental rele	ease measures	
6.1. Personal precautions, prote	ective equipment and emergency procedures	
	Avoid formation of dust. Wear suitable respiratory equipment when necessary.	
6.2. Environmental precautions		
	No environmental requirements.	
6.3. Methods and material for co	ontainment and cleaning up	
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, l	labelled container.
6.4. Reference to other sections		
	See section [2, 8 & 13] for further information.	
SECTION 7: Handling and a		
SECTION 7: Handling and s		
7.1. Precautions for safe handling		
	Ensure adequate ventilation of the working area. Avoid formation of dust. In case ventilation, wear suitable respiratory equipment.	of insufficient
	Do not eat, drink or smoke in areas where this product is used or stored. Wash h handling the product.	ands after
7.2. Conditions for safe storage	e, including any incompatibilities	
	Keep containers tightly closed.	
7.3. Specific end use(s)	·	
	Foundry material.	
SECTION 8: Exposure contr	rols/nersonal protection	
8.1. Control parameters	Total protocular	
	Ensure adequate ventilation of the working area.	
8.1.1. Exposure Limit Values	• • • • • • • • • • • • • • • • • • • •	
Quartz	WEL 8-hr limit ppm: WEL 8-hr limit mg/m3:	0.3
addi 2	WEL 15 min limit ppm: WEL 15 min limit mg/m3:	
	WEL 8-hr limit mg/m3 total - WEL 15 min limit mg/m3 total	
	inhalable dust: inhalable dust: inhalable dust: WEL 8-hr limit mg/m3 total - WEL 15 min limit mg/m3 total	
	respirable dust: respirable dust:	
8.2. Exposure controls		
8.2.1. Appropriate engineering	Ensure adequate ventilation of the working area.	
controls		
8.2.2. Individual protection measures	Wear protective clothing.	
Eye / face protection	In case of splashing, wear:. Approved safety goggles. safety glasses with side-sh	iields.



Revision 1
Revision date 2016-07-05

8.2. Exposure controls

•	Skin protection - Handprotection	Wear suitable gloves.
	Respiratory protection	Suitable respiratory equipment.
	8.2.3. Environmental exposure	Not normally required.
	controls	
	Occupational exposure	Appropriate local exhaust ventilation is required.
	controls	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
	Off white
Odour	Slight
Relative density	2.38 (H2O = 1 @ 20 °C)
Partition coefficient	
рН	No data available
Melting point	No data available
	No data available
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Autoignition temperature	Not applicable.
Fat Solubility	Not applicable.
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	Not applicable.
Benzene Content	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic	Not applicable.
compounds)	

SECTION 10: Stability and reactivity

To The Today Try		
	Not applicable.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
	No Significant Hazard.	
10.4. Conditions to avoid		
	No Significant Hazard.	
10.5. Incompatible materials		
	No Significant Hazard.	

Revision 1
Revision date 2016-07-05

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity
Skin corrosion/irritation
Serious eye damage/irritation
Respiratory or skin
sensitisation
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT-single exposure
STOT-repeated exposure

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Chronic effects

Prolonged inhalation of respirable crystalline silica

In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:

"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."

(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)

There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).

Aspiration hazard

Repeated or prolonged exposure

Not applicable. Based on available data, the classification criteria are not met.

Inhalation of dust may cause shortness of breath.

SECTION 12: Ecological information

12.2. Persistence and degradability

Not applicable.

12.3. Bioaccumulative potential

Does not bioaccumulate.

Partition coefficient

	Plasticast PT investment No data available
--	--

12.4. Mobility in soil

Not determined.

12.5. Results of PBT and vPvB assessment

Revision 1
Revision date 2016-07-05

12.5. Results of PBT and vPvB a	12.5. Results of PBT and vPvB assessment	
	Not determined.	
12.6. Other adverse effects		
	Not applicable.	
SECTION 13: Disposal cons	iderations	
13.1. Waste treatment methods		
	Dispose of in compliance with all. local and national regulations.	
Disposal methods		
	Contact a licensed waste disposal company.	
Disposal of packaging		
	Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.	
Further information		
	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.	
SECTION 14: Transport info	rmation	
Further information		
	The product is not classified as dangerous for carriage.	
SECTION 15: Regulatory inf	ormation	
15.1. Safety, health and environ	mental regulations/legislation specific for the substance or mixture	
Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.	

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Training

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

Social Dialogue on Respirable Crystalline Silica

A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide,



Revision 1
Revision date 2016-07-05

	are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on	
	request from EUROSIL, the European Association of Industrial Silica Producers,.	
	STOT RE1: H372 - DANGER - Causes damage to lungs through prolonged or repeated exposure by inhalation.	
Revision	This document differs from the previous version in the following areas:.	
	2 - 2.1. Classification of the substance or mixture.	
	2 - 2.1.2. Classification - EC 1272/2008.	
	2 - Hazard Statement.	
	2 - Precautionary Statement: Prevention.	
	2 - Precautionary Statement: Response.	
	2 - Precautionary Statement: Storage.	
	15 - Labelling.	
	15 - Risk phrases.	
Text of risk phrases in Sec	·	
3	R37/38 - Irritating to respiratory system and skin.	
	R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.	
Text of Hazard Statements Section 3	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.	
Further information	Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	