

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/7

Ultra-Vest(R) BANDUST(TM) & Ultra-Vest(R) MAXX BANDUST(TM) investment

Revision

Revision date 2019-07-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	Ultra-Vest(R) BANDUST(TM) & Ultra-Vest(R) MAXX BANDUST(TM) investment	
1.2. Relevant identified uses o	f the substance or mixture and uses advised against	
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites;	
Description	Foundry material.	
1.3. Details of the supplier of t	he safety data sheet	
Company	Ransom & Randolph	
Address	3535 Briarfield Boulevard, PO Box 1570 Maumee, Ohio 43537 USA	
Web	www.ransom-randolph.com	
Telephone	+1 (419) 865-9497	
Fax	+1 (419) 865-9997	
Email	RR.SDS@dentsply.com	
Email address of the competent person	RR.SDS@dentsply.com	
1.4. Emergency telephone nur	nber	
Emergency telephone number	USA +1 419 865 9497	
Company	Ransom & Randolph Co.	

08:00-17:00 (US Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC	STOT RE 1: H372;
1272/2008	

2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash (hands) thoroughly after handling.
	P270 - Do no eat, drink or smoke when using this product.
Precautionary Statement: Response	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

Revision 2
Revision date 2019-07-05

2.3. Other hazards

Other hazards Product contains respirable crystalline silica (RCS).

Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. Classification (%w/w)
Silica (cristobalite)		14464-46-1	238-455-4		40 - 50% STOT RE 1: H372;
Quartz		14808-60-7	238-878-4		20 - 30% STOT RE 1: H372;
Calcium sulfate (Plaster of Paris)		26499-65-0			20 - 30%

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

Quartz "fine fraction" >= 10 % w/w / CAS 14808-60-7, EC No 238-878-4 / STOT RE1: H372.

Silica (Cristobalite) "fine fraction" >= 10 % w/w / CAS 14464-46-1, EC No 238-455-4 / STOT

RE1: H372.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash with soap and water.	
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.	
Eye contact	Seek medical attention if irritation or symptoms persist.	
Skin contact	Seek medical attention if irritation or symptoms persist.	
Ingestion	Seek medical attention if irritation or symptoms persist.	

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear suitable protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Revision

Revision date 2019-07-05

6.1. Personal precautions, pro	otective equipment and emergency proce	dures
	Avoid formation of dust. Wear suitable res	spiratory equipment when necessary.
6.2. Environmental precaution	ns	
	No environmental requirements.	
6.3. Methods and material for	containment and cleaning up	
	Avoid raising dust. Clean the area using a	a vacuum cleaner. Transfer to suitable, labelled container.
6.4. Reference to other section	ns	
	See section [2, 8 & 13] for further informa	tion.
SECTION 7: Handling and	storage	
7.1. Precautions for safe hand	lling	
	Ensure adequate ventilation of the workin ventilation, wear suitable respiratory equi	ng area. Avoid formation of dust. In case of insufficient pment.
	Do not eat, drink or smoke in areas where handling the product.	e this product is used or stored. Wash hands after
7.2. Conditions for safe storage	ge, including any incompatibilities	
	Keep containers tightly closed.	
7.3. Specific end use(s)		
	Foundry material.	
SECTION 8: Exposure con	trols/personal protection	
8.1. Control parameters		
	Ensure adequate ventilation of the working	g area.
8.1.1. Exposure Limit Values		
Calcium sulfate (Plaster of	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
Paris)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust: WEL 8-hr limit mg/m3 total 4	inhalable dust: WEL 15 min limit mg/m3 total -
Quartz	respirable dust: WEL 8-hr limit ppm:	respirable dust: WEL 8-hr limit mg/m3: .1
Qual L2	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total	WEL 15 min limit mg/m3 total -
	inhalable dust: WEL 8-hr limit mg/m3 total -	inhalable dust: WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
8.2. Exposure controls		
Exposure delition		

Wear protective clothing.

Wear suitable gloves.

Ensure adequate ventilation of the working area.

In case of splashing, wear:. Approved safety goggles. safety glasses with side-shields.

ChemSoft EH&S

8.2.1. Appropriate

measures

engineering controls 8.2.2. Individual protection

Eye / face protection Skin protection -

Revision date 2019-07-05

8.2. Exposure controls

<u> </u>	
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Powder Off white Colour Odour Slight **Odour threshold** Not applicable. Melting point No data available Freezing Point Not applicable. Initial boiling point Not applicable. Flash point Not applicable. Evaporation rate Not applicable. Flammability (solid, gas) Not applicable. Vapour pressure Not applicable. Vapour density Not applicable. Relative density 2.5 **Fat Solubility** Not applicable. Partition coefficient Not applicable. Autoignition temperature Not applicable.

Viscosity No data available

Explosive properties Not applicable. **Oxidising properties**

Not applicable.

Solubility

Slightly soluble in water

9.2. Other information

Conductivity No data available No data available Surface tension Gas group Not applicable. Benzene Content Not applicable. Lead content Not applicable. **VOC (Volatile organic** Not applicable. compounds)

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
	No Significant Hazard.	
40.4.0		

10.4. Conditions to avoid

No Significant Hazard.

10.5. Incompatible materials

No Significant Hazard.

Not applicable.

Revision

2

Revision date 2019-07-05

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation
Serious eye damage/irritation
Respiratory or skin
sensitisation
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT-single exposure

STOT-repeated exposure

Acute toxicity

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Carcinogenic effects.

Not applicable. Based on available data, the classification criteria are not met.

Not applicable. Based on available data, the classification criteria are not met.

Chronic effects

Prolonged inhalation of respirable crystalline silica

In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:

"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."

(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)

There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).

Aspiration hazard Repeated or prolonged exposure Not applicable. Based on available data, the classification criteria are not met.

Inhalation of dust may cause shortness of breath.

11.1.4. Toxicological Information

Ultra-Vest(R) BANDUST(TM) & Ultra-Vest(R) MAXX BANDUST(TM) investment Oral Rat LD50: >5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Ultra-Vest(R) BANDUST(TM) &
Ultra-Vest(R) MAXX
BANDUST(TM) investment

Fish LC50/96h: 10000.000 mg/l

12.2. Persistence and degradability

Not applicable.

12.3. Bioaccumulative potential

Does not bioaccumulate.

Partition coefficient

Revision date 2019-07-05

	Nevision date 2010 01 00
Partition coefficient	
	Ultra-Vest(R) BANDUST(TM) & Not applicable.
	Ultra-Vest(R) MAXX BANDUST(TM) investment
12.4. Mobility in soil	
	Not determined.
12.5. Results of PBT and vPvB	assessment
	Not determined.
12.6. Other adverse effects	
	Not applicable.
SECTION 13: Disposal con	siderations
13.1. Waste treatment methods	s
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.
Further information	
	For disposal within the EC, the appropriate code according to the European Waste Catalogue
	(EWC) should be used.
SECTION 14: Transport information	
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es)	
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	·
	The product is not classified as dangerous for carriage.
14.6. Special precautions for user	
	The product is not classified as dangerous for carriage.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	
	The product is not classified as dangerous for carriage.
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory in	formation
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No
Nogulations	1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,
	Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and

Revision

2

Revision date 2019-07-05

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Training

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

Social Dialogue on Respirable Crystalline Silica

A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers.

STOT RE1: H372 - DANGER - Causes damage to lungs through prolonged or repeated exposure by inhalation.

Revision

This document differs from the previous version in the following areas:.

2 - 2.1. Classification of the substance or mixture.

15 - Labelling.

15 - Hazard Statement.

Text of Hazard Statements in Section 3

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.